

# Package ‘eventPred’

January 21, 2024

**Title** Event Prediction

**Version** 0.2.4

**Date** 2024-01-20

**Description**

Predicts enrollment and events at the design or analysis stage using specified enrollment and time-to-event models through simulations.

**License** GPL (>= 2)

**Encoding** UTF-8

**RoxygenNote** 7.3.0

**Imports** dplyr (>= 1.1.0), rlang (>= 1.0.6), plotly (>= 4.10.1), survival (>= 2.41-3), splines (>= 3.5.0), Matrix (>= 1.2-14), mvtnorm (>= 1.1-3), rstpm2 (>= 1.6.1), numDeriv (>= 2016.8-1.1), purrr (>= 1.0.2), flexsurv (>= 2.2.2), erify (>= 0.4.0), stats (>= 3.5.0), shiny (>= 1.7.1)

**Suggests** knitr, rmarkdown, testthat (>= 3.0.0)

**Depends** R (>= 3.5.0)

**VignetteBuilder** knitr

**LazyData** true

**URL** <https://github.com/kaifenglu/eventPred>

**BugReports** <https://github.com/kaifenglu/eventPred/issues>

**NeedsCompilation** no

**Author** Kaifeng Lu [aut, cre] (<<https://orcid.org/0000-0002-6160-7119>>)

**Maintainer** Kaifeng Lu <[kaifenglu@gmail.com](mailto:kaifenglu@gmail.com)>

**Repository** CRAN

**Date/Publication** 2024-01-21 15:30:02 UTC

## R topics documented:

finalData . . . . .	2
fitDropout . . . . .	3
fitEnrollment . . . . .	4
fitEvent . . . . .	6
getPrediction . . . . .	8
interimData1 . . . . .	12
interimData2 . . . . .	13
predictEnrollment . . . . .	13
predictEvent . . . . .	15
pwexpreg . . . . .	18
runShinyApp . . . . .	19
summarizeObserved . . . . .	19

<b>Index</b>	<b>21</b>
--------------	-----------

---

finalData	<i>Final enrollment and event data after achieving the target number of events</i>
-----------	--

---

### Description

A data frame with 300 rows and 7 columns:

trialsdt The trial start date  
 usubjid The unique subject ID  
 randdt The randomization date  
 treatment The treatment group number  
 treatment\_description Description of the treatment group  
 time The day of event or censoring since randomization  
 event The event indicator: 1 for event, 0 for non-event  
 dropout The dropout indicator: 1 for dropout, 0 for non-dropout  
 cutoffdt The cutoff date

For ongoing subjects, both event and dropout are equal to 0.

### Usage

```
finalData
```

### Format

An object of class `tbl_df` (inherits from `tbl`, `data.frame`) with 300 rows and 9 columns.

---

fitDropout	<i>Fit time-to-dropout model</i>
------------	----------------------------------

---

### Description

Fits a specified time-to-dropout model to the dropout data.

### Usage

```
fitDropout(
  df,
  dropout_model = "exponential",
  piecewiseDropoutTime = 0,
  k_dropout = 0,
  scale_dropout = "hazard",
  showplot = TRUE,
  by_treatment = FALSE,
  covariates = NULL
)
```

### Arguments

df	The subject-level dropout data, including time and dropout. The data should also include treatment coded as 1, 2, and so on, and treatment_description for fitting the dropout model by treatment.
dropout_model	The dropout model used to analyze the dropout data which can be set to one of the following options: "exponential", "Weibull", "log-logistic", "log-normal", "piecewise exponential", "model averaging", or "spline". The model averaging uses the $\exp(-bic/2)$ weighting and combines Weibull and log-normal models. The spline model of Royston and Parmar (2002) assumes that a transformation of the survival function is modeled as a natural cubic spline function of log time. By default, it is set to "exponential".
piecewiseDropoutTime	A vector that specifies the time intervals for the piecewise exponential dropout distribution. Must start with 0, e.g., c(0, 60) breaks the time axis into 2 event intervals: [0, 60) and [60, Inf). By default, it is set to 0.
k_dropout	The number of inner knots of the spline. The default k_dropout=0 gives a Weibull, log-logistic or log-normal model, if scale_dropout is "hazard", "odds", or "normal", respectively. The knots are chosen as equally-spaced quantiles of the log uncensored survival times. The boundary knots are chosen as the minimum and maximum log uncensored survival times.
scale_dropout	If "hazard", the log cumulative hazard is modeled as a spline function. If "odds", the log cumulative odds is modeled as a spline function. If "normal", -qnorm(S(t)) is modeled as a spline function.
showplot	A Boolean variable to control whether or not to show the fitted time-to-dropout survival curve. By default, it is set to TRUE.

by_treatment	A Boolean variable to control whether or not to fit the time-to-dropout data by treatment group. By default, it is set to FALSE.
covariates	The names of baseline covariates from the input data frame to include in the dropout model, e.g., c("age", "sex"). Factor variables need to be declared in the input data frame.

### Value

A list of results from the model fit including key information such as the dropout model, `model`, the estimated model parameters, `theta`, the covariance matrix, `vtheta`, as well as the Akaike Information Criterion, `aic`, and Bayesian Information Criterion, `bic`.

If the piecewise exponential model is used, the location of knots used in the model, `piecewiseDropoutTime`, will be included in the list of results.

If the model averaging option is chosen, the weight assigned to the Weibull component is indicated by the `w1` variable.

If the spline option is chosen, the knots and scale will be included in the list of results.

When fitting the dropout model by treatment, the outcome is presented as a list of lists, where each list element corresponds to a specific treatment group.

The fitted time-to-dropout survival curve is also returned.

### Author(s)

Kaifeng Lu, <kaifenglu@gmail.com>

### References

Patrick Royston and Mahesh K. B. Parmar. Flexible parametric proportional-hazards and proportional-odds models for censored survival data, with application to prognostic modelling and estimation of treatment effects. *Stat in Med.* 2002; 21:2175-2197.

### Examples

```
dropout_fit <- fitDropout(df = interimData2,
                        dropout_model = "exponential")
```

---

fitEnrollment

*Fit enrollment model*

---

### Description

Fits a specified enrollment model to the enrollment data.

**Usage**

```
fitEnrollment(
  df,
  enroll_model = "b-spline",
  nknots = 0,
  accrualTime = 0,
  showplot = TRUE
)
```

**Arguments**

df	The subject-level enrollment data, including trialsdt, randdt and cutoffdt.
enroll_model	The enrollment model which can be specified as "Poisson", "Time-decay", "B-spline", or "Piecewise Poisson". By default, it is set to "B-spline".
nknots	The number of inner knots for the B-spline enrollment model. By default, it is set to 0.
accrualTime	The accrual time intervals for the piecewise Poisson model. Must start with 0, e.g., c(0, 30) breaks the time axis into 2 accrual intervals: [0, 30) and [30, Inf). By default, it is set to 0.
showplot	A Boolean variable to control whether or not to show the fitted enrollment curve. By default, it is set to TRUE.

**Details**

For the time-decay model, the mean function is  $\mu(t) = \mu/\delta*(t - 1/\delta*(1 - \exp(-\delta*t)))$  and the rate function is  $\lambda(t) = \mu/\delta*(1 - \exp(-\delta*t))$ . For the B-spline model, the daily enrollment rate is approximated as  $\lambda(t) = \exp(B(t)*\theta)$ , where  $B(t)$  represents the B-spline basis functions.

**Value**

A list of results from the model fit including key information such as the enrollment model, model, the estimated model parameters, theta, the covariance matrix, vtheta, the Akaike Information Criterion, aic, and the Bayesian Information Criterion, bic, as well as the design matrix x for the B-spline enrollment model, and accrualTime for the piecewise Poisson enrollment model.

The fitted enrollment curve is also returned.

**Author(s)**

Kaifeng Lu, <kaifenglu@gmail.com>

**References**

Xiaoxi Zhang and Qi Long. Stochastic modeling and prediction for accrual in clinical trials. Stat in Med. 2010; 29:649-658.

**Examples**

```
enroll_fit <- fitEnrollment(df = interimData1, enroll_model = "b-spline",
                           nknots = 1)
```

---

<code>fitEvent</code>	<i>Fit time-to-event model</i>
-----------------------	--------------------------------

---

**Description**

Fits a specified time-to-event model to the event data.

**Usage**

```
fitEvent(
  df,
  event_model = "model averaging",
  piecewiseSurvivalTime = 0,
  k = 0,
  scale = "hazard",
  showplot = TRUE,
  by_treatment = FALSE,
  covariates = NULL
)
```

**Arguments**

- |                                    |   |
|------------------------------------|---|
| <code>df</code>                    | The subject-level event data, including time and event. The data should also include treatment coded as 1, 2, and so on, and <code>treatment_description</code> for fitting the event model by treatment.   |
| <code>event_model</code>           | The event model used to analyze the event data which can be set to one of the following options: "exponential", "Weibull", "log-logistic", "log-normal", "piecewise exponential", "model averaging", or "spline". The model averaging uses the $\exp(-bic/2)$ weighting and combines Weibull and log-normal models. The spline model of Royston and Parmar (2002) assumes that a transformation of the survival function is modeled as a natural cubic spline function of log time. By default, it is set to "model averaging". |
| <code>piecewiseSurvivalTime</code> | A vector that specifies the time intervals for the piecewise exponential survival distribution. Must start with 0, e.g., <code>c(0, 60)</code> breaks the time axis into 2 event intervals: <code>[0, 60)</code> and <code>[60, Inf)</code> . By default, it is set to 0.   |
| <code>k</code>                     | The number of inner knots of the spline. The default <code>k=0</code> gives a Weibull, log-logistic or log-normal model, if <code>scale</code> is "hazard", "odds", or "normal", respectively. The knots are chosen as equally-spaced quantiles of the log uncensored survival times. The boundary knots are chosen as the minimum and maximum log uncensored survival times.   |



---

getPrediction	<i>Enrollment and event prediction</i>
---------------	--

---

**Description**

Performs enrollment and event prediction by utilizing observed data and specified enrollment and event models.

**Usage**

```
getPrediction(  
  df = NULL,  
  to_predict = "enrollment and event",  
  target_n = NA,  
  target_d = NA,  
  enroll_model = "b-spline",  
  nknots = 0,  
  lags = 30,  
  accrualTime = 0,  
  enroll_prior = NULL,  
  event_model = "model averaging",  
  piecewiseSurvivalTime = 0,  
  k = 0,  
  scale = "hazard",  
  event_prior = NULL,  
  dropout_model = "exponential",  
  piecewiseDropoutTime = 0,  
  k_dropout = 0,  
  scale_dropout = "hazard",  
  dropout_prior = NULL,  
  fixedFollowup = FALSE,  
  followupTime = 365,  
  pilevel = 0.9,  
  nyears = 4,  
  nreps = 500,  
  showEnrollment = TRUE,  
  showEvent = TRUE,  
  showDropout = FALSE,  
  showOngoing = FALSE,  
  showssummary = TRUE,  
  showplot = TRUE,  
  by_treatment = FALSE,  
  ngroups = 1,  
  alloc = NULL,  
  treatment_label = NULL,  
  covariates_event = NULL,  
  event_prior_with_covariates = NULL,
```



```

    covariates_dropout = NULL,
    dropout_prior_with_covariates = NULL
)

```

## Arguments

df	The subject-level enrollment and event data, including trialsdt, usubjid, randdt, and cutoffdt for enrollment prediction, and, additionally, time, event, and dropout for event prediction. The data should also include treatment coded as 1, 2, and so on, and treatment_description for enrollment and event prediction by treatment. By default, it is set to NULL for enrollment and event prediction at the design stage.
to_predict	Specifies what to predict: "enrollment only", "event only", or "enrollment and event". By default, it is set to "enrollment and event".
target_n	The target number of subjects to enroll in the study.
target_d	The target number of events to reach in the study.
enroll_model	The enrollment model which can be specified as "Poisson", "Time-decay", "B-spline", or "Piecewise Poisson". By default, it is set to "B-spline".
nknots	The number of inner knots for the B-spline enrollment model. By default, it is set to 0.
lags	The day lags to compute the average enrollment rate to carry forward for the B-spline enrollment model. By default, it is set to 30.
accrualTime	The accrual time intervals for the piecewise Poisson model. Must start with 0, e.g., c(0, 30) breaks the time axis into 2 accrual intervals: [0, 30) and [30, Inf). By default, it is set to 0.
enroll_prior	The prior of enrollment model parameters.
event_model	The event model used to analyze the event data which can be set to one of the following options: "exponential", "Weibull", "log-logistic", "log-normal", "piecewise exponential", "model averaging", or "spline". The model averaging uses the $\exp(-bic/2)$ weighting and combines Weibull and log-normal models. By default, it is set to "model averaging".
piecewiseSurvivalTime	A vector that specifies the time intervals for the piecewise exponential survival distribution. Must start with 0, e.g., c(0, 60) breaks the time axis into 2 event intervals: [0, 60) and [60, Inf). By default, it is set to 0.
k	The number of inner knots of the spline event model of Royston and Parmar (2002). The default $k=0$ gives a Weibull, log-logistic or log-normal model, if scale is "hazard", "odds", or "normal", respectively. The knots are chosen as equally-spaced quantiles of the log uncensored survival times. The boundary knots are chosen as the minimum and maximum log uncensored survival times.
scale	If "hazard", the log cumulative hazard is modeled as a spline function. If "odds", the log cumulative odds is modeled as a spline function. If "normal", $-qnorm(S(t))$ is modeled as a spline function.
event_prior	The prior of event model parameters.

dropout_model	The dropout model used to analyze the dropout data which can be set to one of the following options: "none", "exponential", "Weibull", "log-logistic", "log-normal", "piecewise exponential", "model averaging", or "spline". The model averaging uses the $\exp(-bic/2)$ weighting and combines Weibull and log-normal models. By default, it is set to "exponential".
piecewiseDropoutTime	A vector that specifies the time intervals for the piecewise exponential dropout distribution. Must start with 0, e.g., $c(0, 60)$ breaks the time axis into 2 event intervals: $[0, 60)$ and $[60, Inf)$ . By default, it is set to 0.
k_dropout	The number of inner knots of the spline dropout model of Royston and Parmar (2002). The default $k\_dropout=0$ gives a Weibull, log-logistic or log-normal model, if $scale\_dropout$ is "hazard", "odds", or "normal", respectively. The knots are chosen as equally-spaced quantiles of the log uncensored survival times. The boundary knots are chosen as the minimum and maximum log uncensored survival times.
scale_dropout	If "hazard", the log cumulative hazard is modeled as a spline function. If "odds", the log cumulative odds is modeled as a spline function. If "normal", $-qnorm(S(t))$ is modeled as a spline function.
dropout_prior	The prior of dropout model parameters.
fixedFollowup	A Boolean variable indicating whether a fixed follow-up design is used. By default, it is set to FALSE for a variable follow-up design.
followupTime	The follow-up time for a fixed follow-up design, in days. By default, it is set to 365.
pilevel	The prediction interval level. By default, it is set to 0.90.
nyears	The number of years after the data cut for prediction. By default, it is set to 4.
nreps	The number of replications for simulation. By default, it is set to 500.
showEnrollment	A Boolean variable to control whether or not to show the number of enrolled subjects. By default, it is set to TRUE.
showEvent	A Boolean variable to control whether or not to show the number of events. By default, it is set to TRUE.
showDropout	A Boolean variable to control whether or not to show the number of dropouts. By default, it is set to FALSE.
showOngoing	A Boolean variable to control whether or not to show the number of ongoing subjects. By default, it is set to FALSE.
showsummary	A Boolean variable to control whether or not to show the prediction summary. By default, it is set to TRUE.
showplot	A Boolean variable to control whether or not to show the plots. By default, it is set to TRUE.
by_treatment	A Boolean variable to control whether or not to predict by treatment group. By default, it is set to FALSE.
ngroups	The number of treatment groups for enrollment prediction at the design stage. By default, it is set to 1. It is replaced with the actual number of treatment groups in the observed data if $df$ is not NULL.

alloc	The treatment allocation in a randomization block. By default, it is set to NULL, which yields equal allocation among the treatment groups.
treatment_label	The treatment labels for treatments in a randomization block for design stage prediction. It is replaced with the treatment_description in the observed data if df is not NULL.
covariates_event	The names of baseline covariates from the input data frame to include in the event model, e.g., c("age", "sex"). Factor variables need to be declared in the input data frame.
event_prior_with_covariates	The prior of event model parameters in the presence of covariates.
covariates_dropout	The names of baseline covariates from the input data frame to include in the dropout model, e.g., c("age", "sex"). Factor variables need to be declared in the input data frame.
dropout_prior_with_covariates	The prior of dropout model parameters in the presence of covariates.

## Details

For the time-decay model, the mean function is  $\mu(t) = \mu/\delta*(t - 1/\delta*(1 - \exp(-\delta*t)))$  and the rate function is  $\lambda(t) = \mu/\delta*(1 - \exp(-\delta*t))$ . For the B-spline model, the daily enrollment rate is approximated as  $\lambda(t) = \exp(B(t)*\theta)$ , where  $B(t)$  represents the B-spline basis functions.

The `enroll_prior` variable should be a list that includes `model` to specify the enrollment model (poisson, time-decay, or piecewise poisson), `theta` and `vtheta` to indicate the parameter values and the covariance matrix. One can use a very small value of `vtheta` to fix the parameter values. For the piecewise Poisson enrollment model, the list should also include `accrualTime`. It should be noted that the B-spline model is not appropriate for use as prior.

For event prediction by treatment with prior information, the `event_prior` (`dropout_prior`) variable should be a list with one element per treatment. For each treatment, the element should include `model` to specify the event (dropout) model (exponential, weibull, log-logistic, log-normal, or piecewise exponential), `theta` and `vtheta` to indicate the parameter values and the covariance matrix. For the piecewise exponential event (dropout) model, the list should also include `piecewiseSurvivalTime` (`piecewiseDropoutTime`) to indicate the location of knots. It should be noted that the model averaging and spline options are not appropriate for use as prior.

If the event prediction is not by treatment while the prior information is given by treatment, then each element of `event_prior` (`dropout_prior`) should also include `w` to specify the weight of the treatment in a randomization block. If the prediction is not by treatment and the prior is given for the overall study, then `event_prior` (`dropout_prior`) is a flat list with `model`, `theta`, and `vtheta`. For the piecewise exponential event (dropout) model, it should also include `piecewiseSurvivalTime` (`piecewiseDropoutTime`) to indicate the location of knots.

For analysis-stage enrollment and event prediction, the `enroll_prior`, `event_prior`, and `dropout_prior` are either set to NULL to use the observed data only, or specify the prior distribution of model parameters to be combined with observed data likelihood for enhanced modeling flexibility.

**Value**

A list that includes the fits of observed data models, as well as simulated enrollment data for new subjects and simulated event data for ongoing and new subjects.

**Author(s)**

Kaifeng Lu, <kaifenglu@gmail.com>

**Examples**

```
# Event prediction after enrollment completion

pred <- getPrediction(
  df = interimData2, to_predict = "event only",
  target_d = 200,
  event_model = "weibull",
  dropout_model = "exponential",
  pilevel = 0.90, nreps = 100)
```

---

interimData1

*Interim enrollment and event data before enrollment completion*


---

**Description**

A data frame with 225 rows and 9 columns:

trialsdt The trial start date  
 usubjid The unique subject ID  
 randdt The randomization date  
 treatment The treatment group number  
 treatment\_description Description of the treatment group  
 time The day of event or censoring since randomization  
 event The event indicator: 1 for event, 0 for non-event  
 dropout The dropout indicator: 1 for dropout, 0 for non-dropout  
 cutoffdt The cutoff date

For ongoing subjects, both event and dropout are equal to 0.

**Usage**

```
interimData1
```

**Format**

An object of class `tbl_df` (inherits from `tbl`, `data.frame`) with 224 rows and 9 columns.

---

interimData2	<i>Interim enrollment and event data after enrollment completion</i>
--------------	--

---

### Description

A data frame with 300 rows and 7 columns:

trialsdt The trial start date

usubjid The unique subject ID

randdt The randomization date

treatment The treatment group number

treatment\_description Description of the treatment group

time The day of event or censoring since randomization

event The event indicator: 1 for event, 0 for non-event

dropout The dropout indicator: 1 for dropout, 0 for non-dropout

cutoffdt The cutoff date

For ongoing subjects, both event and dropout are equal to 0.

### Usage

```
interimData2
```

### Format

An object of class `tbl_df` (inherits from `tbl`, `data.frame`) with 300 rows and 9 columns.

---

predictEnrollment	<i>Predict enrollment</i>
-------------------	---------------------------

---

### Description

Utilizes a pre-fitted enrollment model to generate enrollment times for new subjects and provide a prediction interval for the expected time to reach the enrollment target.

**Usage**

```

predictEnrollment(
  df = NULL,
  target_n,
  enroll_fit,
  lags = 30,
  pilevel = 0.9,
  nyears = 4,
  nreps = 500,
  showssummary = TRUE,
  showplot = TRUE,
  by_treatment = FALSE,
  ngroups = 1,
  alloc = NULL,
  treatment_label = NULL
)

```

**Arguments**

<code>df</code>	The subject-level enrollment data, including <code>trialsdt</code> , <code>randdt</code> and <code>cutoffdt</code> . The data should also include <code>treatment</code> coded as 1, 2, and so on, and <code>treatment_description</code> for prediction by treatment group. By default, it is set to <code>NULL</code> for enrollment prediction at the design stage.
<code>target_n</code>	The target number of subjects to enroll in the study.
<code>enroll_fit</code>	The pre-fitted enrollment model used to generate predictions.
<code>lags</code>	The day lags to compute the average enrollment rate to carry forward for the B-spline enrollment model. By default, it is set to 30.
<code>pilevel</code>	The prediction interval level. By default, it is set to 0.90.
<code>nyears</code>	The number of years after the data cut for prediction. By default, it is set to 4.
<code>nreps</code>	The number of replications for simulation. By default, it is set to 500.
<code>showssummary</code>	A Boolean variable to control whether or not to show the prediction summary. By default, it is set to <code>TRUE</code> .
<code>showplot</code>	A Boolean variable to control whether or not to show the prediction plot. By default, it is set to <code>TRUE</code> .
<code>by_treatment</code>	A Boolean variable to control whether or not to predict enrollment by treatment group. By default, it is set to <code>FALSE</code> .
<code>ngroups</code>	The number of treatment groups for enrollment prediction at the design stage. By default, it is set to 1. It is replaced with the actual number of treatment groups in the observed data if <code>df</code> is not <code>NULL</code> .
<code>alloc</code>	The treatment allocation in a randomization block. By default, it is set to <code>NULL</code> , which yields equal allocation among the treatment groups.
<code>treatment_label</code>	The treatment labels for treatments in a randomization block for design stage prediction. It is replaced with the <code>treatment_description</code> in the observed data if <code>df</code> is not <code>NULL</code> .

**Details**

The `enroll_fit` variable can be used for enrollment prediction at the design stage. A piecewise Poisson model can be parameterized through the time intervals, `accrualTime`, which is treated as fixed, and the enrollment rates in the intervals, `accrualIntensity`, the log of which is used as the model parameter. For the homogeneous Poisson, time-decay, and piecewise Poisson models, `enroll_fit` is used to specify the prior distribution of model parameters, with a very small variance being used to fix the parameter values. It should be noted that the B-spline model is not appropriate for use during the design stage.

During the enrollment stage, `enroll_fit` is the enrollment model fit based on the observed data. The fitted enrollment model is used to generate enrollment times for new subjects.

**Value**

A list of prediction results, which includes important information such as the median, lower and upper percentiles for the estimated time to reach the target number of subjects, as well as simulated enrollment data for new subjects. The data for the prediction plot is also included within the list.

**Author(s)**

Kaifeng Lu, <kaifenglu@gmail.com>

**References**

Xiaoxi Zhang and Qi Long. Stochastic modeling and prediction for accrual in clinical trials. *Stat in Med.* 2010; 29:649-658.

**Examples**

```
# Enrollment prediction at the design stage

enroll_pred <- predictEnrollment(
  target_n = 300,
  enroll_fit = list(model = "piecewise poisson",
                    theta = log(26/9*seq(1, 9)/30.4375),
                    vtheta = diag(9)*1e-8,
                    accrualTime = seq(0, 8)*30.4375),
  pilevel = 0.90, nreps = 100)
```

---

predictEvent

*Predict event*

---

**Description**

Utilizes pre-fitted time-to-event and time-to-dropout models to generate event and dropout times for ongoing subjects and new subjects. It also provides a prediction interval for the expected time to reach the target number of events.

**Usage**

```

predictEvent(
  df = NULL,
  target_d,
  newSubjects = NULL,
  event_fit = NULL,
  dropout_fit = NULL,
  fixedFollowup = FALSE,
  followupTime = 365,
  pilevel = 0.9,
  nyears = 4,
  nreps = 500,
  showEnrollment = TRUE,
  showEvent = TRUE,
  showDropout = FALSE,
  showOngoing = FALSE,
  showssummary = TRUE,
  showplot = TRUE,
  by_treatment = FALSE,
  covariates_event = NULL,
  event_fit_with_covariates = NULL,
  covariates_dropout = NULL,
  dropout_fit_with_covariates = NULL
)

```

**Arguments**

<code>df</code>	The subject-level enrollment and event data, including <code>trialsdt</code> , <code>usubjid</code> , <code>randdt</code> , <code>cutoffdt</code> , <code>time</code> , <code>event</code> , and <code>dropout</code> . The data should also include <code>treatment</code> coded as 1, 2, and so on, and <code>treatment_description</code> for by-treatment prediction. By default, it is set to <code>NULL</code> for event prediction at the design stage.
<code>target_d</code>	The target number of events to reach in the study.
<code>newSubjects</code>	The enrollment data for new subjects including <code>draw</code> and <code>arrivalTime</code> . The data should also include <code>treatment</code> for prediction by treatment. By default, it is set to <code>NULL</code> , indicating the completion of subject enrollment.
<code>event_fit</code>	The pre-fitted event model used to generate predictions.
<code>dropout_fit</code>	The pre-fitted dropout model used to generate predictions. By default, it is set to <code>NULL</code> , indicating no dropout.
<code>fixedFollowup</code>	A Boolean variable indicating whether a fixed follow-up design is used. By default, it is set to <code>FALSE</code> for a variable follow-up design.
<code>followupTime</code>	The follow-up time for a fixed follow-up design, in days. By default, it is set to 365.
<code>pilevel</code>	The prediction interval level. By default, it is set to 0.90.
<code>nyears</code>	The number of years after the data cut for prediction. By default, it is set to 4.



nreps	The number of replications for simulation. By default, it is set to 500. If newSubjects is not NULL, the number of draws in newSubjects should be nreps.
showEnrollment	A Boolean variable to control whether or not to show the number of enrolled subjects. By default, it is set to TRUE.
showEvent	A Boolean variable to control whether or not to show the number of events. By default, it is set to TRUE.
showDropout	A Boolean variable to control whether or not to show the number of dropouts. By default, it is set to FALSE.
showOngoing	A Boolean variable to control whether or not to show the number of ongoing subjects. By default, it is set to FALSE.
showsummary	A Boolean variable to control whether or not to show the prediction summary. By default, it is set to TRUE.
showplot	A Boolean variable to control whether or not to show the prediction plot. By default, it is set to TRUE.
by_treatment	A Boolean variable to control whether or not to predict event by treatment group. By default, it is set to FALSE.
covariates_event	The names of baseline covariates from the input data frame to include in the event model, e.g., c("age", "sex"). Factor variables need to be declared in the input data frame.
event_fit_with_covariates	The pre-fitted event model with covariates used to generate event predictions for ongoing subjects.
covariates_dropout	The names of baseline covariates from the input data frame to include in the dropout model, e.g., c("age", "sex"). Factor variables need to be declared in the input data frame.
dropout_fit_with_covariates	The pre-fitted dropout model with covariates used to generate dropout predictions for ongoing subjects.

## Details

To ensure successful event prediction at the design stage, it is important to provide the newSubjects data set.

To specify the event (dropout) model used during the design-stage event prediction, the event\_fit (dropout\_fit) should be a list with one element per treatment. For each treatment, the element should include w to specify the weight of the treatment in a randomization block, model to specify the event model (exponential, weibull, log-logistic, log-normal, or piecewise exponential), theta and vtheta to indicate the parameter values and the covariance matrix. For the piecewise exponential event (dropout) model, the list should also include piecewiseSurvivalTime (piecewiseDropoutTime) to indicate the location of knots. It should be noted that the model averaging and spline options are not appropriate for use during the design stage.

Following the commencement of the trial, we obtain the event model fit and the dropout model fit based on the observed data, denoted as event\_fit and dropout\_fit, respectively. These fitted

models are subsequently utilized to generate event and dropout times for both ongoing and new subjects in the trial.

### Value

A list of prediction results which includes important information such as the median, lower and upper percentiles for the estimated day and date to reach the target number of events, as well as simulated event data for both ongoing and new subjects. The data for the prediction plot is also included within this list.

### Author(s)

Kaifeng Lu, <kaifenglu@gmail.com>

### References

Emilia Bagiella and Daniel F. Heitjan. Predicting analysis times in randomized clinical trials. *Stat in Med.* 2001; 20:2055-2063.

Gui-shuang Ying and Daniel F. Heitjan. Weibull prediction of event times in clinical trials. *Pharm Stat.* 2008; 7:107-120.

### Examples

```
# Event prediction after enrollment completion

event_fit <- fitEvent(df = interimData2,
                    event_model = "piecewise exponential",
                    piecewiseSurvivalTime = c(0, 140, 352))

dropout_fit <- fitDropout(df = interimData2,
                        dropout_model = "exponential")

event_pred <- predictEvent(df = interimData2, target_d = 200,
                          event_fit = event_fit$event_fit,
                          dropout_fit = dropout_fit$dropout_fit,
                          pilevel = 0.90, nreps = 100)
```

---

pwexpreg

*Piecewise exponential regression*

---

### Description

Obtains the maximum likelihood estimates for piecewise exponential regression.

### Usage

```
pwexpreg(time, event, J, tcut, q, x)
```

**Arguments**

time	The survival time.
event	The event indicator.
J	The number of time intervals.
tcut	A vector that specifies the endpoints of time intervals for the baseline piecewise exponential survival distribution. Must start with 0, e.g., c(0, 60) breaks the time axis into 2 event intervals: [0, 60) and [60, Inf). By default, it is set to 0.
q	The number of columns of the covariates matrix.
x	The covariates matrix (excluding the intercept).

**Value**

The maximum likelihood estimates and the associated covariance matrix, AIC and BIC.

---

runShinyApp	<i>Run Shiny app</i>
-------------	----------------------

---

**Description**

Runs the event prediction Shiny app.

**Usage**

```
runShinyApp()
```

**Author(s)**

Kaifeng Lu, <kweifenglu@gmail.com>

---

summarizeObserved	<i>Summarize observed data</i>
-------------------	--------------------------------

---

**Description**

Provides an overview of the observed data, including the trial start date, data cutoff date, enrollment duration, number of subjects enrolled, number of events and dropouts, number of subjects at risk, cumulative enrollment and event data, daily enrollment rates, and Kaplan-Meier plots for time to event and time to dropout.



# Index

## \* datasets

- finalData, [2](#)
- interimData1, [12](#)
- interimData2, [13](#)

- finalData, [2](#)
- fitDropout, [3](#)
- fitEnrollment, [4](#)
- fitEvent, [6](#)

- getPrediction, [8](#)

- interimData1, [12](#)
- interimData2, [13](#)

- predictEnrollment, [13](#)
- predictEvent, [15](#)
- pwexpreg, [18](#)

- runShinyApp, [19](#)

- summarizeObserved, [19](#)